

Notified body No. 2812

Certificate of Constancy of Performance 2812-CPR-AD5376

In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product

C24V Concealed Door Closer

Intended use: For use on fire / smoke compartmentation single leaf and double leaf doors CONCEALED IN DOOR & CONCEALED IN TRANSOM APPLICATIONS.

le all all		111
Essential characteristics	Performance Mechanical Test Evidence: WIL	Harmonised technical specification
	316449, WIL 316449T & 324426.	
	Fire Test Evidence: 153131 Iss 6	
Self closing		
5.2.1 General 5.2.2 Durability	500,000 test cycles	
5.2.3 Closing moment	Pass size 2 to 4	
5.2.4 Opening moment	Pass size 2 to 4	
5.2.5 Efficiency	>50% size 2	
5.2.5 Efficiency	>60% size 4	
,		
5.2.6 Closing time	Pass	EN 1154:1996/A1:2002/AC:2006
5.2.7 Angles of operation	Grade 3, > 105°	
5.2.8 Overload performance	Pass	
5.2.9 Temperature dependence	-15°C to +40°C	
5.2.10 Fluid leakage	Pass	
5.2.11 Damage	Pass	
5.2.12 Latch control	Pass	
5.2.13 Back check (optional)	NPD	
5.2.14 Delayed closing (optional)	NPD	
5.2.15 Adjustable closing force (optional)	Pass	
5.2.16 Zero position (double action door closers only)	NPD	
5.2.18 Fire/smoke door suitability	Pass	
Essential characteristics	Performance	Harmonised technical specification
Durability of Self Closing 5.2.2 Durability	500,000 test cycles	
5.2.17.1 corrosion	Grade 3 (96 hours)	
5.2.17.2 corrosion	Pass	EN 1154:1996/A1:2002/AC:2006
Dangerous Substances Annex ZA3	Pass: the materials in the door closer do not contain or release any dangerous substances in excess of the maximum levels specified in existing European material standards or any national regulations	



Certificate of Constancy of Performance 2812-CPR-AD5376

Placed on the Market under the Name of

Freeman & Pardoe Tything Road, Arden Forest Industrial Estate, Alcester, Warwickshire, B49 6ES

and produced in the manufacturing plant

K/019

This is coded format and the information is held by the Notified Body

This certificate attests that all provisions concerning the Assessment and Verification of Constancy of Performance described in Annex ZA of the standard(s):

EN 1154:1996/A1:2002/AC:2006

Under System 1 for the performance set out in this certificate are applied and that the Factory Production Control conducted by the manufacturer is assessed to ensure the constancy of performance of the construction product.

This certificate was first issued on 15/12/2020 and will remain valid as long as neither the harmonised standard, the Construction Product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, or unless suspended or withdrawn by the Notified Product Certification Body.

Valid to: 20/02/2021

ERO Project Reference: EROWF11261

Paul Duggan Certification Manager



CSF408-NL 5.0